

# SAFETY DATA

Issue 4 December 2004

## SDS No 132

# E70 EPOXY GROUT BASE COMPONENT

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING.

Product Name: E70 Epoxy Grout  
Use: Base component of three part epoxy resin.  
Company: Tecroc Products Limited  
Holly Lane Industrial Estate  
Atherstone,  
Warks, CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

### 2. COMPOSITION / INFORMATION ON INGREDIENTS.

**Light Hydrocarbon Oil/Surfactant Mixture.** Not classified as hazardous.  
**Epoxy Resin.** Average Molecular Weight <700.  
CAS 25068-38-6 EEC Symbol Xi R Phrases 36/38,43  
**Cresyl Glycidyl Ether** CAS 26447-14-3  
EEC Symbol Xi R Phrase 36/38,43

### 3. HAZARDS IDENTIFICATION

Irritating to eyes and skin.  
May cause sensitisation by skin contact.

### 4. FIRST AID MEASURES

#### Eye Contact

Rinse immediately with water for at least 15 minutes.  
Get medical attention urgently.

#### Skin Contact

Wash with soap and water or skin cleansing cream. Do not use organic solvents.

#### Inhalation

Move into fresh air.

#### Ingestion

Get medical attention. Give water to drink **DO NOT** induce vomiting. In case of spontaneous vomiting ensure vomit can drain freely to avoid suffocation.

### 5. FIRE FIGHTING MEASURES

#### Suitable Extinguishing Media

Water Mist, Foam, Carbon Dioxide, Dry Powder.

#### Unsuitable Extinguishing Media

High pressure water jet.

#### Exposure Hazards

Prevent contaminated water from entering drains, soil or surface water. Dispose of contaminated water and soil according to local and national regulations. Release of toxic fumes may occur. Fire fighters should wear self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions

Do not breathe vapour. Wear suitable protective clothing, gloves and eye/face protection.

#### Environmental Precautions

Prevent contamination of soil, drains and surface water.

#### Methods for Cleaning

Take up with absorbent inert material. Place in closable containers. Dispose of as waste.

### 7. HANDLING AND STORAGE

#### Handling

Irritant, sensitising. Do not breathe vapour. Avoid ignition sources. Ensure adequate ventilation. Do not eat, drink or smoke at work place.

#### Storage

Keep in original container. Keep dry and at room temperature.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Protective Measures

No special measures required.

#### Occupational Exposure Limits

Mineral oil mist 8 Hour TWA; 5mg/m<sup>3</sup>

#### Respiratory Protection

In case of insufficient ventilation wear suitable respiratory equipment.

#### Hand Protection

Wear suitable gloves (eg PVC).

#### Eye Protection

Wear suitable safety glasses to BSEN 166.

#### Skin Protection

Wear overalls and closed footwear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point/Range: N/A  
Boiling Point/Range: >200°C  
Oxidising Properties: N/A  
Autoflammability: N/A  
Solubility in Water: Insoluble.  
Vapour Pressure: 1Pa @ 20°C  
Partition Coefficient: N/A  
Explosive properties: N/A  
Appearance: Straw coloured liquid.  
Odour: Slight  
Density: 1.15g/cm<sup>3</sup> @ 20°C  
Flashpoint: 138°C DIN51758  
Ignition: N/A  
pH value: N/A  
Viscosity: 500-600 mPas @ 25°C.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**

# SAFETY DATA

## SDS No 132

# E70 EPOXY GROUT

## BASE COMPONENT

Issue 4 December 2004

### 10. STABILITY AND REACTIVITY

Stability: Stable, thermal decomposition >200°C  
Conditions to avoid: Static charges  
Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

Hazardous Decomposition Products: Thermal decomposition or burning may release oxides of carbon and other hazardous gases or vapours.

### 11. TOXICOLOGICAL INFORMATION

Information used to assess health effects: LD50 acute oral toxicity in rats: 5000mg/kg. Eye irritation test on rabbits: Irritant. Skin irritation test on rabbits: Irritant. Skin sensitization on guinea pigs: Causes sensitization.

#### Health Effects

##### Eyes

Causes irritation.

##### Skin

Causes irritation.

##### Inhalation

Can cause respiratory irritation.

##### Ingestion

Causes irritation of mouth throat and digestive tract.

##### Chronic

Repeated skin contact can lead to skin disorders.

##### Other

Classified as a skin sensitizer.

### 12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.

Mobility: Mobile liquid.  
Solubility: Insoluble in water.  
Persistence and Degradability: Not expected to be biodegradable.  
Bioaccumulative Potential: Expected to be bioaccumulative.

### 13. DISPOSAL CONSIDERATIONS

Disposal must be carried out under guidance from local and national legislation.  
Waste From Residues/Unused Product: Dispose of via a licensed waste contractor to a licensed disposal site.  
Contaminated Packaging: Dispose of via a licensed waste contractor.

### 14. TRANSPORT INFORMATION

Proper shipping name: Environmentally hazardous substance liquid n.o.s.  
RID/ADR : UN 3082 CL9 PGIII  
IMDG-Code : UN 3082 CL9 PGIII  
IATA : UN 3082 CL9 PGIII  
Flashpoint : 138°C

### 15. REGULATORY INFORMATION

**Symbol:** Xi

#### **Contains:**

Epoxy resin average molecular weight <700.  
Cresyl Glycidyle Ether.

#### **Risk Phrases:**

R36/38 Irritating to eyes and skin.  
R43 May cause sensitisation by skin contact.

#### **Safety Phrases:**

S1/2: Keep locked up and out of the reach of children.  
S28: After contact with skin, wash immediately with plenty of soap and water.  
S37/39 Wear suitable gloves and eye/face protection.

### 16. OTHER INFORMATION

These data sheets are given in connection with the product being used for the purposes outlined in the Product Technical Data Sheet, available from Tecroc Products Ltd on request. Use of the above product for other purposes may result in risks not given above.

If the product is to be used by a third party at work it is the duty of the initial recipient to ensure that the third party is supplied with the data given above.

Employers have the duty to inform employees and others who may be affected of any hazards given in the data above and any precautions that should be adopted.

Users of the product should undertake their own assessment of work place risks as required by the Health and Safety Legislation.

Further copies of this Safety Data Sheet are available from Tecroc Products Ltd.

Safety Data Sheet According to  
Directive 91/155/EEC CHIP Regulations.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**

# E70 EPOXY GROUT FILLER COMPONENT

### 1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY / UNDERTAKING.

Product Name E70 Epoxy Grout.  
Use Filler component of three  
part epoxy resin grout.  
Company Tecroc Products Ltd  
Holly Lane Ind Est  
Atherstone,  
Warks, CV9 2RN  
Telephone 01827 711755  
Fax 01827 711330

### 2. COMPOSITION / INFORMATION ON INGREDIENTS.

Mixture of silica sands, inert fillers and pigments. Not  
classified as hazardous.

### 3. HAZARDS IDENTIFICATION

Air born dust.

### 4. FIRST AID MEASURES

#### Eye Contact

Rinse immediately with water for at least 15 minutes. If  
irritation persists get medical attention.

#### Skin contact

Wash with soap and water.

#### Inhalation

Move into fresh air.

#### Ingestion

Wash mouth with plenty of water. **DO NOT** induce  
vomiting. In case of spontaneous vomiting ensure vomit  
can drain freely to avoid suffocation. Seek medical  
attention.

### 5. FIRE FIGHTING MEASURES

#### Suitable Extinguishing Media

None required as not flammable.

#### Exposure Hazards

None as not flammable.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions

Wear suitable protective clothing, gloves and  
eye/face protection.

#### Environmental Precautions

Prevent contamination of soil, drains and surface  
water.

#### Methods for Cleaning

Take up material. Avoid air born dust. Place in  
closable containers. Dispose of as waste.

### 7. HANDLING AND STORAGE

#### Handling

Ensure adequate ventilation. Do not breathe dust  
and avoid eye contact.

#### Storage

Keep in original container. Keep dry.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Protective Measures

No special measures required.

#### Occupational Exposure Measures

Amorphous Silica 8Hour TWA; Total inhalable  
dust OES 6mg/m<sub>3</sub> Respirable dust OES 2.4mg/m<sub>3</sub>

#### Respiratory Protection

In case of insufficient ventilation wear suitable  
respiratory equipment.

#### Hand Protection

Wear suitable gloves (eg PVC)

#### Eye Protection

Wear suitable safety glasses to BSEN 166

#### Skin Protection

Wear overalls and closed footwear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point/Range	N/A
Boiling Point/Range	N/A
Oxidising Properties	N/A
Autoflammability	N/A
Solubility in Water	Insoluble
Vapour Pressure	N/A
Partition Coefficient	N/A
Explosive Properties	N/A
Appearance	Pale coloured granular powder
Odour	None
Density	Bulk Density 1.6 approx
Flashpoint	N/A
Ignition	N/A
pH Value	N/A
Viscosity	N/A

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

# E70 EPOXY GROUT FILLER COMPONENT

### 10. STABILITY AND REACTIVITY

Stability	Stable
Conditions to avoid	Static discharges
Materials to avoid	None known
Hazardous Decomposition	
Products	None known

### 11. TOXICOLOGICAL INFORMATION

#### Health Effects

##### Eyes

May cause irritation.

##### Skin

May cause irritation.

##### Inhalation

Can cause respiratory irritation.

##### Ingestion

May cause irritation of the mouth, throat and digestive tract.

##### Chronic

Respirable dust fraction, if inhaled over a prolonged period, constitutes a health hazard. Such inhalation can give rise to fibrosis of the lung.

##### Other

None known.

### 12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.

Mobility	Granular Powder
Solubility	Insoluble.
Persistence and Degradability	Not applicable.
Bioaccumulative Potential	Not applicable.

### 13. DISPOSAL CONSIDERATIONS

For large quantities disposal must be carried out under guidance from local and national legislation. Small quantities can be disposed of as common waste via a licensed waste contractor.

### 14. TRANSPORT INFORMATION

Not classified as dangerous for transport.

### 15. REGULATORY INFORMATION

#### Risk Phrases

None

#### Safety Phrases

S1/2 Keep locked up and out of the reach of children. S22 Do not breathe dust .S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S37/39 Wear suitable gloves and eye/face protection.

### 16. OTHER INFORMATION

These data sheets are given in connection with the product being used for the purposes outlined in the Product Technical Data Sheet, available from Tecroc Products Ltd on request. Use of the above product for other purposes may result in risks not given above.

If the product is to be used by a third party at work, it is the duty of the initial recipient to ensure that the third party is supplied with the data given above.

Employers have the duty to inform employees and others who may be effected of any hazards given in the data above and any precautions which should be adopted.

Users of the product should undertake their own assessment of work place risks as required by the Health and Safety Legislation.

Further copies of this Safety Data Sheet are available from Tecroc Products Ltd

Safety Data Sheet According to  
Directive 91/155/EEC CHIP Regulations.

# SAFETY DATA

Issue 5 December 2004

SDS No 133

## E70 EPOXY GROUT HARDENER COMPONENT

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING.

Product Name: E70 Epoxy Grout  
Use: Hardener component of three  
part epoxy resin primer.  
Company: Tecroc Products Limited  
Holly Lane Industrial Estate  
Atherstone,  
Warks, CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

### 2. COMPOSITION / INFORMATION ON INGREDIENTS.

**Modified Aliphatic Polyamine preparation.**  
**Diethylenetriamine** CAS 111-40-0 EEC Symbol C  
Risk Phrases R21/22-34-43. **Benzyl Alcohol** CAS 100-  
51-6 EEC Symbol Xn R Phrases 20/22

### 3. HAZARDS IDENTIFICATION

Harmful by inhalation, in contact with skin and if  
swallowed. Causes burns. May cause sensitisation by  
skin contact.

### 4. FIRST AID MEASURES

#### Eye Contact

Rinse immediately with water for at least 15 minutes.  
Get medical attention urgently.

#### Skin Contact

Wash with soap and water or skin cleansing cream. Do  
not use organic solvents.

#### Inhalation

Move into fresh air.

#### Ingestion

Get medical attention. Give water to drink **DO NOT**  
induce vomiting. In case of spontaneous vomiting  
ensure vomit can drain freely to avoid suffocation.

### 5. FIRE FIGHTING MEASURES

#### Suitable Extinguishing Media

Water Mist, Foam, Carbon Dioxide, Dry Powder.

#### Unsuitable Extinguishing Media

High pressure water jet.

#### Exposure Hazards

Prevent contaminated water from entering drains, soil  
or surface water. Dispose of contaminated water and  
soil according to local and national regulations. Release  
of toxic fumes may occur. Fire fighters should wear  
self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions

Do not breathe vapour. Wear suitable protective  
clothing, gloves and eye/face protection.

#### Environmental Precautions

Prevent contamination of soil, drains and surface water.

#### Methods for Cleaning

Take up with absorbent inert material. Place in closable  
containers. Dispose of as waste.

### 7. HANDLING AND STORAGE

#### Handling

Causes burns, sensitizing. Do not breathe vapour.  
Avoid ignition sources. Avoid skin and eye contact.  
Ensure adequate ventilation. Do not eat, drink or smoke  
at work place.

#### Storage

Keep away from food and drink. Keep in original  
container. Keep dry and at room temperature.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Protective Measures

No special measures required.

#### Occupational Exposure Limits

None assigned.

#### Respiratory Protection

In case of insufficient ventilation wear suitable  
respiratory equipment.

#### Hand Protection

Wear suitable gloves (eg PVC).

#### Eye Protection

Wear suitable safety glasses to BSEN 166.

#### Skin Protection

Wear overalls and closed footwear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point/Range: N/A  
Boiling Point/Range: 191°C  
Oxidising Properties: N/A  
Autoflammability: N/A  
Solubility in Water: Partly Soluble @ 20°C  
Vapour Pressure: 100 Pa @ 20°C  
Partition Coefficient: N/A  
Explosive properties: N/A  
Appearance: Liquid  
Odour: Smell of ammonia  
Density: c/a 1 gram per cc @ 25°C  
Flashpoint: 113°C DIN 51758  
Ignition: N/A  
pH value: N/A  
Viscosity: 40-80 mPas @ 25°C.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**

# SAFETY DATA

## SDS No 133

# E70 EPOXY GROUT

## HARDENER COMPONENT

Issue 5 December 2004

### 10. STABILITY AND REACTIVITY

Stability:	Stable, thermal decomposition >200°C
Conditions to avoid:	Static discharges
Materials to avoid:	Strong oxidising agents. Strong acids. Strong bases.
Hazardous Decomposition Products:	Ammonia, oxides of nitrogen, oxides of carbon and other hazardous gases or vapours.

### 11. TOXICOLOGICAL INFORMATION

Information used to assess health effects: LD50 acute oral toxicity in rats: 2000mg/kg. Eye irritation test on rabbits: Corrosive. Skin irritation test on rabbits: Corrosive. Skin sensitization on guinea pigs: May cause sensitization.

#### Health Effects

##### Eyes

Severe irritation and burns.

##### Skin

Causes irritation and burns.

##### Inhalation

Respiratory irritation.

##### Ingestion

Severe damage to mouth, throat and digestive tract.

##### Chronic

Repeated skin contact cause burns.

##### Other

Classified as corrosive.

### 12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.

Mobility:	Mobile liquid.
Solubility:	Miscible with water.
Persistence and Degradability:	Not expected to be biodegradable.
Bioaccumulative Potential:	Expected to be bioaccumulative.

### 13. DISPOSAL CONSIDERATIONS

Disposal must be carried out under guidance from local and national legislation.

Waste from Residues/Unused Product: Dispose of via a licensed waste contractor to a licensed disposal site.

Contaminated Packaging: Dispose of via a licensed waste contractor.

### 14. TRANSPORT INFORMATION

Proper Shipping Name:	Corrosive Liquid n.o.s.
RID/ADR :	UN 1760 CL8 PGIII
IMDG-Code :	UN 1760 CL8 PGIII
ICAO :	UN 1760 CL8 PGIII
Flashpoint :	113°C DIN 51758

### 15. REGULATORY INFORMATION

**Symbol:** C

#### Contains:

**Diethylenetriamine and Benzyl Alcohol**

#### Risk Phrases:

R20/22 Harmful by inhalation and if swallowed.

R34 Causes burns: R43 May cause sensitisation by skin contact.

#### Safety Phrases:

S1/2: Keep locked up and out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of soap and water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

### 16. OTHER INFORMATION

Directive 91/155/EEC CHIP Regulations. These data sheets are given in connection with the product being used for the purposes outlined in the Product Technical Data Sheet, available from Tecroc Products Ltd on request. Use of the above product for other purposes may result in risks not given above.

If the product is to be used by a third party at work it is the duty of the initial recipient to ensure that the third party is supplied with the data given above.

Employers have the duty to inform employees and others who may be affected of any hazards given in the data above and any precautions that should be adopted.

Users of the product should undertake their own assessment of work place risks as required by the Health and Safety Legislation.

Further copies of this Safety Data Sheet are available from Tecroc Products Ltd.

Safety Data Sheet According to Directive 91/155/EEC CHIP Regulations.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**