

# KERBFIX PE BASE COMPONENT

## 1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY / UNDERTAKING.

|              |  |
|--------------|--|
| Product Name | Kerbfix PE   |
| Use          | Base component of polyester resin rapid setting mortar.                    |
| Company      | Tecroc Products Ltd<br>Holly Lane Ind Est<br>Atherstone,<br>Warks, CV9 2RN |
| Telephone    | 01827 711755   |
| Fax          | 01827 711330   |

## 2. COMPOSITION / INFORMATION ON INGREDIENTS.

Polyester Resin EEC – symbol Xi R Phrases 36/38, 43  
Styrene Monomer EEC – symbol Xn R  
Phrases 10,20, 36/38

## 3. HAZARDS IDENTIFICATION

Flammable, Harmful by inhalation, Irritating to eyes and skin, may cause sensitisation by skin contact.

## 4. FIRST AID MEASURES

### Eye Contact

Rinse immediately with water for at least 15 minutes. Get medical attention urgently.

### Skin contact

Wash with soap and water – do not use organic solvents.

### Inhalation

Move into fresh air. Seek medical advice

### Ingestion

Wash mouth with plenty of water. **DO NOT** induce vomiting. In case of spontaneous vomiting ensure vomit can drain freely to avoid suffocation. Seek medical attention urgently.

## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media

Water Mist, Foam, Carbon Dioxide, Dry Powder

### Unsuitable Extinguishing Media

High pressure water jets.

### Exposure Hazards

Prevent contaminated water from entering drains, soil or surface water. Dispose of contaminated water and soil according to local and national regulations. Release of toxic fumes may occur. Fire fighters should wear self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Do not breathe vapour. Wear suitable protective clothing, gloves and eye/face protection.

### Environmental Precautions

Prevent contamination of soil, drains and surface water.

### Methods for Cleaning

Take up with absorbent insert material. Place in closable containers. Dispose of as waste.

## 7. HANDLING AND STORAGE

### Handling

Harmful, sensitising. Do not breathe vapour. Avoid ignition sources. Ensure adequate ventilation. Do not eat, drink or smoke at work place.

### Storage

Keep in original container. Keep dry. Store in accordance with Highly Flammable Liquids and Liquefied Gases Regulations 1972.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Protective Measures

No special measures required.

### Occupational Exposure Measures

Styrene 8Hour TWA; MEL 430mg/m<sub>3</sub>

### Respiratory Protection

In case of insufficient ventilation wear suitable respiratory equipment.

### Hand Protection

Wear suitable gloves (eg PVC)

### Eye Protection

Wear suitable safety glasses to BSEN 166

### Skin Protection

Wear overalls and closed footwear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                       |                                     |
|-----------------------|-------------------------------------|
| Melting Point/Range   | N/A                                 |
| Boiling Point/Range   | 145°C                               |
| Oxidising Properties  | N/A                                 |
| Autoflammability      | 485°C                               |
| Solubility in Water   | Insoluble                           |
| Vapour Pressure       | 6.2 mbar (styrene)                  |
| Partition Coefficient | N/A                                 |
| Explosive Properties  | Explosive limits 1.1-6.1% (styrene) |
| Appearance            | Yellow Liquid                       |
| Odour                 | Irritant penetrating odour          |
| Density               | 1.05 @ 20°C                         |
| Flashpoint            | 31°C                                |
| Ignition              | Flammable                           |
| pH Value              | N/A                                 |
| Viscosity             | 0.763 Ps @ 20°C                     |

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**

# KERBFIX PE BASE COMPONENT

### 10. STABILITY AND REACTIVITY

|                                  |   |
|----------------------------------|---|
| Stability                        | Stable under temperate storage conditions   |
| Conditions to avoid              | Sources of ignition<br>Static charges.  |
| Materials to avoid               | Strong bases, strong<br>Oxidising agents, copper  |
| Hazardous Decomposition Products | Thermal decomposition or burning may release oxides of carbon and other hazardous gases or vapours. |

### 11. TOXICOLOGICAL INFORMATION

Toxicological information not available. Well known health effects are available industrially.

#### Health Effects

##### Eyes

Can cause irritation.

##### Skin

Causes moderate to severe irritation. Repeated contact can cause sensitisation and dermatitis.

##### Inhalation

Causes respiratory irritation. Can cause nausea and possible narcosis.

##### Ingestion

Causes irritation of the mouth, throat and digestive tract.

##### Chronic

Repeated exposure may lead to tiredness and prolonged reaction time.

##### Other

None known.

### 12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.

|                               |   |
|-------------------------------|---|
| Mobility                      | Mobile Liquid                             |
| Solubility                    | Insoluble in water.                       |
| Persistence and Degradability | Not expected to be readily biodegradable. |
| Bioaccumulative               | Expected to be potential Bioaccumulative. |

### 13. DISPOSAL CONSIDERATIONS

Disposal must be carried out under guidance from local and national legislation. Waste from residues/unused products must be disposed of via a licensed waste contractor to a licensed disposal site. Contaminated Packaging must be disposed of via a licensed waste contractor.

### 14. TRANSPORT INFORMATION

|                       |                   |
|-----------------------|-------------------|
| Proper shipping name: | Resin solution    |
| RID/ADR               | UN1866 CL 3 PGIII |
| IMDG-Code             | UN1866 CL 3 PGIII |
| ICAO                  | UN1866 CL 3 PGIII |
| Flashpoint            | 31°C              |

### 15. REGULATORY INFORMATION

Symbol Xn

#### Contains

Styrene monomer

#### Risk Phrases

R10 Flammable. R20 Harmful by inhalation. R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact.

#### Safety Phrases

S1/2 Keep locked up and out of the reach of children. S23 Do not breathe vapour.

### 16. OTHER INFORMATION

These data sheets are given in connection with the product being used for the purposes outlined in the Product Technical Data Sheet, available from Tecroc Products Ltd on request. Use of the above product for other purposes may result in risks not given above.

If the product is to be used by a third party at work, it is the duty of the initial recipient to ensure that the third party is supplied with the data given above.

Employers have the duty to inform employees and others who may be effected of any hazards given in the data above and any precautions which should be adopted.

Users of the product should undertake their own assessment of work place risks as required by the Health and Safety Legislation.

Further copies of this Safety Data Sheet are available from Tecroc Products Ltd

Safety Data Sheet According to  
Directive 91/155/EEC CHIP Regulations.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**

# KERBFIX PE CATALYSED FILLER COMPONENT

## 1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY / UNDERTAKING.

|              |  |
|--------------|--|
| Product Name | Kerbfix PE   |
| Use          | Hardener & filler component of polyester resin rapid setting mortar.       |
| Company      | Tecroc Products Ltd<br>Holly Lane Ind Est<br>Atherstone,<br>Warks, CV9 2RN |
| Telephone    | 01827 711755   |
| Fax          | 01827 711330   |

## 2. COMPOSITION / INFORMATION ON INGREDIENTS.

Mixture of silica sands, inert fillers and pigments  
Not classified as hazardous.

Dibenzoyl peroxide 20% with inert filler (content  
2% max) Cas 94-36-0 EEC symbol Xi R Phrases  
36/37/38,43

## 3. HAZARDS IDENTIFICATION

Air born dust.

## 4. FIRST AID MEASURES

### Eye Contact

Rinse immediately with water for at least 15  
minutes. Get medical attention if irritation persists.

### Skin contact

Wash with soap and water or skin cleansing cream

### Inhalation

Move into fresh air.

### Ingestion

Wash mouth with plenty of water. **DO NOT**  
induce vomiting. In case of spontaneous vomiting  
ensure vomit can drain freely to avoid suffocation.

## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media

Water Mist, Foam, Carbon Dioxide, Dry Powder

### Unsuitable Extinguishing Media

High pressure water jets.

### Exposure Hazards

Prevent contaminated water from entering drains,  
soil or surface water. Dispose of contaminated  
water and soil according to local and national  
regulations. Release of toxic fumes may occur.  
Fire fighters should wear self-contained breathing  
apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Wear suitable protective clothing, gloves and eye/face  
protection.

### Environmental Precautions

Prevent contamination of soil, drains and surface  
water.

### Methods for Cleaning

Take up material. Avoid air born dust. Place in  
closable containers. Dispose of as waste.

## 7. HANDLING AND STORAGE

### Handling

Ensure adequate ventilation. Do not breathe dust.  
Avoid eye contact.

### Storage

Keep in original container. Keep dry.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Protective Measures

No special measures required.

### Occupational Exposure Measures

Amorphous Silica 8 hour Twa; total inhalable dust Oes  
6.0mg/M\_ Respirable Dust Oes 2.4mg/M\_

### Respiratory Protection

In case of insufficient ventilation wear suitable  
respiratory equipment.

### Hand Protection

Wear suitable gloves (eg PVC)

### Eye Protection

Wear suitable safety glasses to BSEN 166

### Skin Protection

Wear overalls and closed footwear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                       |                              |
|-----------------------|------------------------------|
| Melting Point/Range   | N/A                          |
| Boiling Point/Range   | N/A                          |
| Oxidising Properties  | Oxidising Agent less than 2% |
| Autoflammability      | >380°C                       |
| Solubility in Water   | Insoluble                    |
| Vapour Pressure       | N/A                          |
| Partition Coefficient | N/A                          |
| Explosive Properties  | N/A                          |
| Appearance            | Coloured Granular Powder     |
| Odour                 | Slight, Sweet                |
| Density               | Bulk Density 1.6 appx        |
| Flashpoint            | N/A                          |
| Ignition              | N/A                          |
| pH Value              | N/A                          |
| Viscosity             | N/A                          |

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

# KERBFIX PE CATALYSED FILLER COMPONENT

### 10. STABILITY AND REACTIVITY

|                                  |   |
|----------------------------------|---|
| Stability                        | Stable  |
| Conditions to avoid              | Static discharges.                                  |
| Hazardous Decomposition Products | None expected from Benzoyl Peroxide at less than 2% |

### 11. TOXICOLOGICAL INFORMATION

Information used to assess health effects based on Dibenzoyl Peroxide 78% in water from Benzoylperoxide at less than 2%. Acute Toxicity:- Oral Ld50 Rat:> 5000mg/Kg Inhalation Lc50 Rat:> 24.3mg/L 4 hour exposure – Maximum attainable concentrate.

#### Health Effects

##### Eyes

Can cause irritation.

##### Skin

Can cause irritation.

##### Inhalation

Respiratory irritation.

##### Ingestion

May cause irritation of the mouth, throat and digestive tract.

##### Chronic

Respirable dust fraction, if inhaled over a prolonged period, constitutes a health hazard. Such inhalation can give rise to fibrosis of the lung

##### Other

None known.

### 12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.

|                               |                                    |
|-------------------------------|------------------------------------|
| Mobility                      | Granular Powder                    |
| Solubility                    | Insoluble.                         |
| Persistence and Degradability | Readily biodegradable              |
| Bioaccumulative               | Closed bottle test                 |
|                               | Not thought to be Bioaccumulative. |

### 13. DISPOSAL CONSIDERATIONS

Disposal must be carried out under guidance from local and national legislation. Waste from residues/unused products must be disposed of via a licensed waste contractor to a licensed disposal site. Contaminated Packaging must be disposed of via a licensed waste contractor.

### 14. TRANSPORT INFORMATION

Not classified as dangerous for transport.

### 15. REGULATORY INFORMATION

**Symbol** N/A

#### Contains

Benzoyl Peroxide at less than 2%

#### Risk Phrases

R36/37/38 Irritating to eyes, respiratory system and skin. R43 May cause sensitisation by skin contact.

#### Safety Phrases

S1/2 Keep locked up and out of the reach of children. S26 in case of contact with eyes rinse immediately with plenty of water and seek medical advice. S36/37/39 Wear suitable protective clothing, gloves, eye and face protection.

### 16. OTHER INFORMATION

These data sheets are given in connection with the product being used for the purposes outlined in the Product Technical Data Sheet, available from Tecroc Products Ltd on request. Use of the above product for other purposes may result in risks not given above.

If the product is to be used by a third party at work, it is the duty of the initial recipient to ensure that the third party is supplied with the data given above.

Employers have the duty to inform employees and others who may be effected of any hazards given in the data above and any precautions which should be adopted.

Users of the product should undertake their own assessment of work place risks as required by the Health and Safety Legislation.

Further copies of this Safety Data Sheet are available from Tecroc Products Ltd

Safety Data Sheet According to:  
Directive 91/155/EEC CHIP Regulations.

**Head Office**  
Holly Lane Industrial Estate  
Atherstone  
Warwickshire  
CV9 2RN  
Tel: 01827 711755  
Fax: 01827 711330

**Irish Distributor**  
Construction Chemical Supplies  
Unit 219  
JFK Road JFK Industrial Est  
Dublin 12  
Tel: 00 353 1 450 3896  
Fax: 00 353 1 450 3298

**Web site: [www.tecroc.co.uk](http://www.tecroc.co.uk)**

**E-mail: [enquiries@tecroc.co.uk](mailto:enquiries@tecroc.co.uk)**