

ACRYLIC SEALER

Product Codes

TF08, TF29, Packaging listed overleaf

Description

Acrylic Sealer is a water dispersed acrylic resin latex based hardener and dust proofer for application to concrete floors, screeds and mortars that are friable and dusting. The product may also be used as a dust proofer for blockwork and rendered walls. Acrylic sealer is a single pack product supplied in plastic containers ready for immediate site use. The latex is applied to the floor section using a soft broom or squeegee. For large areas the product may be applied by spray. The low viscosity of Acrylic Sealer enables rapid absorption into the floor surface after application. In most applications two coats are sufficient to reinforce the surface. For very porous screeds a third coat may be required. For very dense surfaces such as granolithics or power floated floors Acrylic sealer should be diluted one to one with clean water.

Uses include:

Reinforcing of friable floor screeds
Dustproofing concrete floors
Dustproofing blockwork and rendered walls
Reinforcement of lime/sand mortars

Typical Properties @ 20°C

Make-up Styrene acrylic copolymer
water dispersion
Appearance Milky white liquid
Odour Faintly sweet
Viscosity Similar to that of water

Specification Outline

Acrylic Sealer as manufactured by Tecroc Products Ltd should be used as the gauging liquid for cementitious mixes. Water may be added to the mixes to adjust workability. The product must be stored, handled and placed strictly in accordance with the manufacturer's instructions.

Quality Assurance

Tecroc Products Ltd is a firm of Assessed Capability. The Company's quality system conforms to BS EN ISO 9001:2000 and is assessed by SGS Ltd Systems and Services Certification.

Instructions For Use

Preparation

Floor areas must be clean and free from all contamination. Sweep or vacuum the area to obtain a dust and debris free surface. The floor must be essentially dry. Walls should be brushed dry to remove dust and loose material.

Application

The acrylic sealer is ready for immediate application straight from the container. Spread the acrylic sealer with a soft brush or broom, a lambswool roller or squeegee. Apply a thin even coat avoiding the formation of puddles. Allow the first coat to be absorbed and dry then apply the second coat. The dwell time will be 4 to 6 hours in dry well ventilated ambient conditions. In damp weather the dwell time will be extended.

Curing

Allow the floor to completely dry before opening to use. The drying period may be 24 hours in warm dry conditions and up to seven days in cold damp conditions.



Grouts

Structural Support
MortarsConcrete Repair
ProductsConstruction
AdhesivesResin Et
Cementitious
AnchorsHighway
Products

Coatings



Waterproofing

Ground
Engineering

Head Office
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2RN
Tel: 01827 711755
Fax: 01827 711330

Irish Distributor
Construction Chemical Supplies
Unit 219
JFK Road JFK Industrial Est
Dublin 12
Tel: 00 353 1 450 3896
Fax: 00 353 1 450 3298

Web site: www.tecroc.co.uk

E-mail: enquiries@tecroc.co.uk

ACRYLIC SEALER

Precautions

Health and Safety

Acrylic Sealer should not come into contact with skin, eyes or be swallowed. Protective glasses should be worn during application. Should Acrylic Sealer come into contact with skin, remove before hardening by washing with soap and water. Should accidental eye contact occur wash with plenty of water and seek medical advice. If swallowed seek medical advice immediately. Do not induce vomiting. For full health and safety data refer to Product Safety Data Sheet

Fire

Acrylic Sealer is non-flammable.

Yield

Coverage

The coverage of the Acrylic Sealer is 2m² to 10m² per litre dependant on substrate roughness and porosity.

Storage And Shelf Life

Acrylic Sealer will have a shelf life of 12 months when kept in dry conditions at a temperature of 5°C to 45°C. Storage at higher temperatures may reduce the shelf life.

Acrylic Sealer must be protected from frost. Shake/stir well before use.

Packaging And Ordering

Acrylic Sealer is supplied in:

5 litre polybottles Product Code TF08

25 litre polybottles Product Code TF29

For further information and sales please contact your local Tecroc Products office as listed below.

Tecroc Products Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Tecroc Products Ltd Terms and Conditions of Sale, copies of which are forwarded on invoice and are available on request. Tecroc Products Ltd endeavours to ensure that the above data and any further advice is correct, however, it cannot accept any direct or indirect liability for the use of its products as such usage is beyond its control.

Head Office
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2RN
Tel: 01827 711755
Fax: 01827 711330

Irish Distributor
Construction Chemical Supplies
Unit 219
JFK Road JFK Industrial Est
Dublin 12
Tel: 00 353 1 450 3896
Fax: 00 353 1 450 3298

Web site: www.tecroc.co.uk

E-mail: enquiries@tecroc.co.uk



Grouts



Structural Support
Mortars



Concrete Repair
Products



Construction
Adhesives



Resin Et
Cementitious
Anchors



Highway
Products



Coatings



Waterproofing



Ground
Engineering