

SOLVENT

Product Codes

TM02, TM 08

Packaging listed overleaf.

Description

Solvent is a synergistic blend of aliphatic and aromatic compounds designed to solvent both polyester and epoxy based products. Solvent may be used as a lubricating trowelling aid to achieve a smooth finish to applied resin based mortars and screeds. Mixing equipment and application tools should always be cleaned with Solvent before setting and hardening has occurred.

Uses include: Obtaining a smooth finish to applied resin based mortars and screeds
Cleaning spillages and snots before hardening has taken place
Cleaning of mixing and application tools

Typical Properties of Solvent

Solvent is based on a blend of Xylene and 1-Methoxypropan-2-ol. This blend acts synergistically to solvent the two main classes of resins used in construction, Polyester and Epoxy.

Solvent is a clear liquid with an aromatic odour. The use of Solvent should always be carried out in a well ventilated area. Solvent is flammable and no smoking should be allowed in the work area.

Specification Outline

Finishing and cleaning operations should be carried out using Solvent as manufactured by Tecroc products Ltd. The product must be stored and used in accordance with the manufacturer's instructions.

Quality Assurance

Tecroc Products Ltd is a firm of Assessed Capability. The Company's quality system conforms to BS EN ISO 9001:2000 and is assessed by SGS Ltd Systems and Services Certification.

Instructions For Use

When using Solvent always wear suitable gloves and work in accordance with the health and safety advice given below and in the Safety Data Sheet.

For use as a finishing medium apply a thin coating to application tools such as trowels by means of a dampened cloth. Repeat the coating regularly as the work progresses.

For use as a cleaning up medium apply a more liberal coating to the particular areas involved and work with a cloth to remove the spills.

After use place used cloths into a sealed container for disposal. Details are given in the Safety Data Sheet.



Grouts



Structural Support
Mortars



Concrete Repair
Products



Construction
Adhesives



Resin Et
Cementitious
Anchors



Highway
Products



Coatings



Waterproofing



Ground
Engineering

Head Office
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2RN
Tel: 01827 711755
Fax: 01827 711330

Irish Distributor
Construction Chemical Supplies
Unit 219
JFK Road JFK Industrial Est
Dublin 12
Tel: 00 353 1 450 3896
Fax: 00 353 1 450 3298

Web site: www.tecroc.co.uk

E-mail: enquiries@tecroc.co.uk

SOLVENT

Storage And Shelf Life

Solvent will have a shelf life of 12 months when kept in moderate ambient conditions. Tins should be tightly closed when not in use. Storage should be in accordance with the Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Packaging And Ordering

Solvent is supplied in screw-capped tins.
 5 litre tin Product Code TM02
 1 litre tin Product Code TM08

For further information and sales please contact your local Tecroc Products office as listed below.

Precautions

Health and Safety

Solvent is classified under the health and safety legislation CHIP Regulations as "harmful". When used with care, as described in the Safety Data Sheet, Solvent is eminently suitable for site use.

Resin based products and solvents may cause allergic reactions in some people. When using Solvent with resins/hardeners wear gloves, use barrier cream on unprotected skin areas and wear eye protection when mixing, using and cleaning. Ensure adequate ventilation to prevent inhalation of vapours. If skin contact occurs remove resin/hardener immediately with cleansing cream and wash with soap and water. **Do not use Solvent.** Should eye contact occur rinse immediately with plenty of clean water and seek medical advice. If, with resin based products, resin/hardener or Solvent is swallowed do not induce vomiting. Seek medical advice immediately.

Full health and safety data are given in Product Safety Data Sheet.

Fire

Solvent is flammable. Should fire occur extinguish with CO₂ or foam.

Tecroc Products Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Tecroc Products Ltd Terms and Conditions of Sale, copies of which are forwarded on invoice and are available on request. Tecroc Products Ltd endeavours to ensure that the above data and any further advice is correct, however, it cannot accept any direct or indirect liability for the use of its products as such usage is beyond its control.



Grouts

Structural Support
MortarsConcrete Repair
ProductsConstruction
AdhesivesResin Et
Cementitious
AnchorsHighway
Products

Coatings



Waterproofing

Ground
Engineering

Head Office
 Holly Lane Industrial Estate
 Atherstone
 Warwickshire
 CV9 2RN
 Tel: 01827 711755
 Fax: 01827 711330

Irish Distributor
 Construction Chemical Supplies
 Unit 219
 JFK Road JFK Industrial Est
 Dublin 12
 Tel: 00 353 1 450 3896
 Fax: 00 353 1 450 3298

Web site: www.tecroc.co.uk

E-mail: enquiries@tecroc.co.uk